

# House Kit

# Radon and indoor air quality system Multi-room connected monitoring

**DOWNLOADS** 









The Airthings House Kit has everything you need to start monitoring the quality of your air, for a healthier home. This multi-room kit includes: Wave, the very first smart radon detector, Wave Mini, for mold risk indication, airborne chemicals, humidity and temperature, and Hub, which brings everything online. Simply connect the Hub to the internet and set up the monitors using the Airthings Wave App. You then gain visibility into indoor air contaminants in multiple rooms in your home, no matter where you are. Data is available via the free Airthings Wave app (iOS/Android) as well as online with the Airthings Dashboard with more advanced analytics options.

#### **COMPLETE HEALTH**

Continuous monitoring of radon is necessary to minimize potential health risks. Compare data and find trends using the Airthings App and online dashboard. When you know what's in your air, small changes to your daily habits make a big difference to your family's health. Users have complete access to long and short term data as well as tips to reduce indoor air hazards, optimize ventilation and save energy.

#### WAVE MINI: MOLD RISK INDICATION

When you see mold, it's too late. We have created an algorithm based on the ASHRAE mold index using our humidity and temp sensors to show mold growth risk before the problem actually occurs. Placement is key, so please see our mold page for more details. airthings.com/mold-risk-indicator

#### **INTEGRATIONS**

The Hub brings your Airthings products online, wirelessly. Live data allows for full integration into your smart home: set alerts, receive air quality measurements, give voice commands, connect to a smart plug or smart product to control your thermostat, air purifier, or humidifier—the options are endless.







# HOUSE KIT SPECIFICATIONS & ADDITIONAL INFORMATION

Bluetooth is used for setup of Hub, Wave 2nd Gen and Wave Mini.

Bluetooth frequency band: 2402 - 2480 MHz

SmartLink wireless protocol is used between Hub, Wave 2nd Gen and Wave Mini

SmartLink frequency band in Europe: 868 - 870 MHz SmartLink frequency band in North America: 902 - 928 MHz

# PACKAGE CONTENT

Wave 2nd Gen Wave Mini Regulatory Information

# **PACKAGE**

Weight: 1250g, 44oz Dimensions: 205x130x165m (See devices for individual sizes of each)

# **REQUIREMENTS**

Ethernet connection for Hub One of the 3 latest major versions of iOS or Android supporting Bluetooth 4.2 or later Bluetooth 4.2 or later to set up your Hub, Wave 2nd Gen and Wave Mini

# **PRODUCT CODES**

EAN: 7090031104207 UPC: 854232008156 SKU: 420

Device serial number: 4200xxxxxx











# WAVE 2ND GEN

### PRODUCT FEATURES

Sensors: Radon, Temp & Humidity Visual indicator: Red/Yellow/Green glow ring

Long battery life:~24 months Supports wall or ceiling mount Free mobile app for iOS and Android Web dashboard Mobile notifications

## IAQ SENSOR SPECIFICATIONS

Sensor sampling interval: 5 minutes Sensor Resolution: Temperature ∓ 0.1°C/F Humidity ∓1%

#### ADDITIONAL INFORMATION

#### PACKAGE CONTENT

Air Quality Detector 2 AA alkaline batteries Instruction Manual Mounting screw

#### **DEVICE**

Weight: 216g, 7.6oz Dimensions: 120x36mm, 4.7x1.4in

#### ADDITIONAL SPECIFICATIONS

Operational Environment: 4°C to 40°C, 39°F to 104°F Power: 2 AA alkaline batteries

## **RADON SPECIFICATIONS**

Radon sampling: Passive diffusion chamber Detection method: Alpha spectrometry Measurement range:  $0 - 20,000 \text{ Bq/m}^3/500 \text{ pCi/L}$ Accuracy/precision at 200 Bq/m<sup>3</sup> / 5.4 pCi/L: After 7 days ~ 10 % After 2 months ~ 5 %

#### PRODUCT CODES

NOT FOR INDIVIDUAL SALE MODEL: 2950

Serial Number: 2950 xxxxxx

# **WAVF MINI**

#### **FUNCTIONS**

Sensors: Mold risk indicator, VOC, Temperature and Humidity Visual feedback: Red/Yellow/Green glow indicator

Long battery life: > 3 years\*

Supports wall mounting or table stand Free mobile app for iOS and Android

Free online dashboard Mobile and web notifications

## **SPECIFICATIONS**

Sensor sampling interval: 5 minutes Sensor Resolution / Accuracy: Temperature: 0.1 / ±1 °C/F Humidity: 1 / ±3 % Settling time: TVOC ~7 days

Operational Environment: 4°C to 40°C, 39°F to 104°F

Power: 3 x AA alkaline batteries Wireless: Bluetooth & SmartLink

# ADDITIONAL INFORMATION

# PACKAGE CONTENT

Air Quality Detector 3 x AA alkaline batteries Instruction Manual Table stand

## **DEVICE**

Weight: 135g, 4.8oz Dimensions: < 80x26mm,

3.14x1in

# PRODUCT CODES

NOT FOR INDIVIDUAL SALE

MODEL: 2920

Device serial number: 2920xxxxxx

# **HUB**

#### **HUB PRODUCT FEATURES**

Remote access to Airthings devices:

Wave 2nd gen (device serial number 2950xxxxxx)

Wave Plus (device serial number 2930xxxxxx)

Wave Mini (device serial number 2920xxxxxx)

One Hub can connect to up to 10 Airthings devices Long-range wireless connection with Airthings SmartLink

Live data streaming to the cloud

Free mobile app for iOS and Android Mounting options: Freestanding or mounted

LED status indicators: Power, cloud and SmartLink connection

# **HUB SPECIFICATIONS**

Operational Environment: 4° - 40°C, 39° - 104°C Power supply: 100-240 V AC / 50-60Hz

Protocols: Airthings SmartLink

Estimated range: Easily covers most residential homes

Connection: Ethernet port











# ADDITIONAL INFORMATION

# HUB PACKAGE CONTENT

Airthings Hub
Ethernet cable
Instruction Manual
Mounting bracket
Rubber bumper pads
Power supply adaptor
US interchangeable supply blade
EU interchangeable supply blade
UK interchangeable supply blade

# DEVICE

Weight: 249g, 8.8 oz Dimensions: 125x125x25mm, 4.9x4.9x1 in

# PRODUCT CODES

NOT FOR INDIVIDUAL SALE MODEL: 2810 Device serial number: 2810xxxxxx









